



STN Series (Plain Steel)

Male NPT X Hose Shank



GEN Series (Plain Steel)

Grooved End X Hose Shank

FEATURES AND ADVANTAGES

- Versatile hose connectors designed to connect hose and pipes of the same thread size.
- Frequently used in low pressure suction and discharge applications, and can be connected to many different types of strainers and couplings.
- Multi-serrated barb design allows for secure hose grip when properly clamped or crimped.

MATERIAL SPECIFICATIONS

- Complies with ASTM A53 B welded pipe.

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/STN-GEN

| Part Number | Size (in) | PSI Rating at 70°F | Weight Each (lbs) | Standard Carton |
|-------------|-----------|--------------------|-------------------|-----------------|
| STN050 | 1/2 | 125 | 0.14 | 25 |
| STN075 | 3/4 | 125 | 0.22 | 25 |
| STN100 | 1 | 125 | 0.32 | 50 |
| STN125 | 1 1/4 | 125 | 0.56 | 20 |
| STN150 | 1 1/2 | 125 | 0.72 | 10 |
| STN200 | 2 | 75 | 1.10 | 40 |
| STN250 | 2 1/2 | 75 | 1.74 | 20 |
| STN300 | 3 | 75 | 2.18 | 12 |
| STN400 | 4 | 75 | 3.22 | 8 |
| STN500 | 5 | 75 | 4.12 | 4 |
| STN600 | 6 | 75 | 12.24 | 4 |

| Part Number | Size (in) | PSI Rating at 70°F | Weight Each (lbs) | Standard Carton |
|-------------|-----------|--------------------|-------------------|-----------------|
| GEN100 | 1 | 125 | 0.58 | 100 |
| GEN125 | 1 1/4 | 125 | 0.62 | 80 |
| GEN150 | 1 1/2 | 125 | 0.86 | 60 |
| GEN200 | 2 | 75 | 1.28 | 50 |
| GEN250 | 2 1/2 | 75 | 2.03 | 20 |
| GEN300 | 3 | 75 | 3.17 | 20 |
| GEN400 | 4 | 75 | 3.88 | 12 |
| GEN600 | 6 | 75 | 14.60 | 4 |
| GEN800 | 8 | 50 | 19.73 | 2 |
| GEN1000 | 10 | 50 | 26.14 | 1 |
| GEN1200 | 12 | 50 | 39.82 | 1 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.