



SPHM Series (Zinc Plated Steel)

Hose Shank x Hose Shank

SSHM Series (316 Stainless Steel)

Hose Shank X Hose Shank

FEATURES AND ADVANTAGES

- Versatile hose connectors designed to connect two hoses together.
- Frequently used in low pressure suction and discharge applications.
- Multi-serrated barb design allows for secure hose grip when properly clamped or crimped.

MATERIAL SPECIFICATIONS

- SPHM Series Complies with ASTM A53 Grade B welded pipe.
- SSHM Series Complies with ASTM A276 grade 316 welded pipe.

VIEW ONLINE



SCAN FOR INFO

or visit

KOA.link/SxHM

Part Number	Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
SPHM050	1/2	250	0.10	100
SPHM062	5/8	200	0.10	100
SPHM075	3/4	200	0.20	100
SPHM100	1	150	0.30	50
SPHM125	1 1/4	150	0.50	50
SPHM150	1 1/2	125	0.60	40
SPHM200	2	75	0.80	35
SPHM250	2 1/2	75	1.70	20
SPHM300	3	50	2.40	15
SPHM400	4	50	2.90	9
SPHM600	6	25	13.20	4
SPHM800	8	25	20.90	2
SPHM1000	10	25	28.63	1
SPHM1200	12	25	48.46	1

Part Number	Size (in)	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
SSHM050	1/2	250	0.11	200
SSHM075	3/4	200	0.22	200
SSHM100	1	150	0.33	100
SSHM125	1 1/4	150	0.56	80
SSHM150	1 1/2	125	0.62	60
SSHM200	2	75	0.85	50
SSHM250	2 1/2	75	1.90	20
SSHM300	3	50	2.75	15
SSHM400	4	50	3.25	9
SSHM600	6	25	15.45	9

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.