



Sandblast Couplings & Accessories
Two Lug Threaded Couplings

SB-AL Series (Aluminum)

SB-BR Series (Brass)

MATERIAL SPECIFICATIONS

- Aluminum – ASTM B26, Grade 713.
- Brass – ASTM B584, Grade C85700.

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/SB-X

Part Number	Hose ID (in)	Hose OD (in)	PSI Rating at 70°F	Gasket	NPT Thread Size (in)	Weight Each (lbs)	Standard Carton
SB-AL1	3/4	1 1/2	150	SBG	1 1/4	0.34	6
SB-AL2	1	1 7/8	150	SBG	1 1/2	0.28	6
SB-AL3	1 1/4	2 3/8	150	SRG-2	1 1/2	1.05	6
SB-BR1	3/4	1 1/2	175	SBG	1 1/4	1.02	6
SB-BR2	1	1 7/8	175	SBG	1 1/2	0.84	6
SB-BR3	1 1/4	2 3/8	175	SRG-2	1 1/2	3.05	6
SB-BR6	2	2 7/8	175	SRG-2	2	4.20	6

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.