



Universal Air Hose Couplings & Accessories

FE Series
Female Threaded Coupling

⚠ WARNING: Not for use
in steam applications

ME Series
Male Threaded Coupling

FEATURES AND ADVANTAGES

- Applications include compressed air systems and pneumatic tools.
- Available in both two lug and four lug styles for quick connecting.
- Designed for compressed air and water service only.

MATERIAL SPECIFICATIONS

- ASTM A27, Grade 1030 Zinc Plated Carbon Steel.
- Complies with Mil-Spec A-A-59553.

VIEW ONLINE



👉 **SCAN FOR INFO**
or visit

[KOA.link/FE-ME](https://koa.link/FE-ME)

Part Number	Female Thread Size (in)	Style	Gasket	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
FE-25	1/4	2 Lug	AHG-75	150	0.32	25
FE-38	3/8	2 Lug	AHG-75	150	0.33	25
FE-50	1/2	2 Lug	AHG-75	150	0.44	25
FE-75	3/4	2 Lug	AHG-75	150	0.48	25
FE-100	1	2 Lug	AHG-75	150	0.52	25
FE-125	1 1/4	4 Lug	AHG-100	150	0.90	10
FE-150	1 1/2	4 Lug	AHG-100	150	1.00	10
FE-200	2	4 Lug	AHG-100	150	1.20	10

Part Number	Male Thread Size (in)	Style	Gasket	PSI Rating at 70°F	Weight Each (lbs)	Standard Carton
ME-25	1/4	2 Lug	AHG-75	150	0.36	25
ME-38	3/8	2 Lug	AHG-75	150	0.40	25
ME-50	1/2	2 Lug	AHG-75	150	0.44	25
ME-75	3/4	2 Lug	AHG-75	150	0.48	25
ME-100	1	2 Lug	AHG-75	150	0.60	25

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.