



## RDA-SS Series (316 Stainless Part D x A) Female Coupler X Male Couple

### GENERAL APPLICATIONS

Kuriyama Camlock Couplings are intended for use in many industrial applications. To learn more, please refer to pages 296-297 in this catalog.

### FEATURES AND ADVANTAGES

- High quality design made to withstand rigorous applications found in industrial markets.
- Stainless steel alloy is analyzed on every melt, and specially designed for high tensile strength, rigidity, and impact resistance.

### MATERIAL SPECIFICATIONS

- ASTM stainless steel alloy.
- Complies with Mil-Spec A-A-59326 for interchangeability.
- 304 stainless steel handles, handle pins, pull rings, and safety clips.
- Buna-N gasket included.

#### VIEW ONLINE



SCAN FOR INFO  
or visit  
[KOA.link/RDA-SS](https://KOA.link/RDA-SS)

Part Number	Female Coupler Size (in)	Male Coupler Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
RDA-SS2010	2	1	150	A666/316	2.73	20
RDA-SS2030	2	3	150	A666/316	3.45	6
RDA-SS3020	3	2	150	A666/316	4.08	4
RDA-SS4030	4	3	150	A666/316	6.41	3
RDA-SS6040	6	4	150	A666/316	12.10	2

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.