

Fixed Orifice, Lightweight, Constant Flow
Fire Hose Nozzle



Viper® SPARTAN®

General Applications:

- Versatile, easy to use and available in four models with over 40 flow and pressure configurations to meet any demand
- Created for the extremes of today's firefighting

Construction:

- Lightweight, hard coat anodized aluminum.
- Durable construction provides low maintenance with no spinning teeth to break.
- Raised protective rubber bumper lug for easy pattern identification.
- Full-time rocker lug swivel with ergonomic pistol grip.

Features and Advantages:

RYLSTATIC® Patented System – The VIPER® SPARTAN® series comes standard with the innovative patented fog pattern called RYLSTATIC®.

RYLSTATIC® is a system that gives you a uniform water fog with smaller water droplets and less friction loss than other traditional systems.

VIPER® SPARTAN® nozzles are designed to operate with a wider fog shield of protection for the firefighter.

Excellent Stream Performance – at a variety of pressures ranging from 50 PSI (3.5 bar) to 100 PSI (7 bar)

Approvals and Standards – The VIPER® SPARTAN® nozzle is National Fire Protection Association (NFPA) 1964 compliant and is manufactured in an ISO 9001 accredited facility. European Standards (EN) 15182-1 and EN15182-2 type 3 Certificates are available by request.

Warranty – 5-year warranty.



Patented Rylstatic® Technology

The ultimate concept in firefighting nozzles!

**Fixed Orifice, Lightweight, Constant Flow
Fire Hose Nozzle**

Viper® Spartan® 300 (2 1/2")

Nozzle Part Number	Nozzle Model Number	Swivel Inlet (In)	50 PSI (gpm)	75 PSI (gpm)	6 BAR (lpm)	100 PSI (gpm)	Weight (each)	
							(lbs)	(kg)
I219933 A-000	VS300	2 1/2	200				5.73	2.60
I219933 A-001	VS300	2 1/2	250				5.73	2.60
I219933 A-003	VS300	2 1/2		200			5.73	2.60
I219933 A-004	VS300	2 1/2		250			5.73	2.60
I219933 A-007	VS300	2 1/2			750	200	5.73	2.60
I219933 A-008	VS300	2 1/2			940	250	5.73	2.60
I219933 A-009	VS300	2 1/2			1030	275	5.73	2.60

Viper® Spartan® 95 (1 1/2") Tip Only

Nozzle Part Number	Nozzle Model Number	Swivel Inlet (In)	50 PSI (gpm)	75 PSI (gpm)	6 BAR (lpm)	100 PSI (gpm)	Weight (each)	
							(lbs)	(kg)
I230027-000	VS95	1 1/2	60				2.10	0.95
I230027-001	VS95	1 1/2	75				2.10	0.95
I230027-002	VS95	1 1/2	95				2.10	0.95
I230027-003	VS95	1 1/2		60			2.10	0.95
I230027-004	VS95	1 1/2		75			2.10	0.95
I230027-005	VS95	1 1/2		95			2.10	0.95
I230027-006	VS95	1 1/2		125			2.10	0.95
I230027-007	VS95	1 1/2			250	60	2.10	0.95
I230027-008	VS95	1 1/2			360	75	2.10	0.95
I230027-009	VS95	1 1/2			400	95	2.10	0.95
I230027-010	VS95	1 1/2			500	125	2.10	0.95