



Viper® FT™

General Applications:

- Ideal for use in demanding fireground applications

Construction:

- Extruded E-Lite alloy, lightweight, hard coated and durable.
- Durable polymer shut-off handles.
- Polyamide fiber reinforced spinning teeth.

Features and Advantages:

- Constant gallonage in all positions.
- Flow ranges from 15 to 200 gpm in 4 models of nozzles.
- BIMATIC system which ensures optimal operating pressure.
- Flush without shutting down nozzle.
- Two-part rubber bumpers provide maximum protection and easier grip.

Approvals and Standards – The VIPER® FT™ nozzle is National Fire Protection Association (NFPA) 1964 compliant and is manufactured in an ISO 9001 accredited facility. European Standards (EN) 15182-1 and EN15182-2 type 3 Certificates are available by request.

Nozzle Part Number	Nozzle Model Number	Swivel Inlet (In)	Nozzle Flow		Length		Weight (each)	
			(gpm)	(lpm)	(in)	(cm)	(lbs)	(kg)
I210458	FT1550 NST	1	15-50	60-200	9.25	23	3.55	1.61
I210461	FT2510 NST	1 1/2	25-100	100-400	9.84	25	4.54	2.06
I210464	FT5016 NST	1 1/2	50-160	200-600	9.80	25	4.54	2.06
I210469	FT8020 NST	1 1/2	80-200	300-800	11.20	28	6.50	2.95
I210471	FT8020 NST	2 1/2	80-200	300-800	13.00	33	7.30	3.31