

Multi-Purpose Nozzles



Viper® VTE™

General Applications:

- General plant wash-down service
- Dust control
- Wildland firefighting

Construction:

- Composite housing with brass stem and rubber bumper.
- Female NST or NPSH threads.
- Fixed teeth.
- Available in Red or Black colors.

Features and Advantages:

- **Adjustable Flow Control** – Twisting nozzle adjusts spray pattern from full stream to misting fog.
- **Impact Resistant** – Rubber bumpers protect nozzle from damage if dropped or dragged.
- **Lightweight** – Compact design reduces worker fatigue.

Approvals and Standards – The VIPER® VTE™ is National Fire Protection Association (NFPA) 1964 compliant and is manufactured in an ISO 9001 accredited facility. European Standards (EN) 15182-1 and EN15182-2 type 3 Certificates are available by request.

| Nozzle Part Number | Nozzle Model Number | Rigid Inlet (In) | Color | Nozzle Flow | | Length | | Weight (each) | |
|--------------------|---------------------|------------------|-------|-------------|-------|--------|------|---------------|------|
| | | | | (gpm) | (lpm) | (in) | (cm) | (lbs) | (kg) |
| I150006C | VTE-1550 | 1 NST | Red | 30 | 125 | 5.30 | 13 | 0.44 | 0.20 |
| I150004C | VTE-1550 | 1 NPSH | Red | 30 | 125 | 5.30 | 13 | 0.44 | 0.20 |
| I150005C | VTE-1550 | 1 NST | Black | 30 | 125 | 5.30 | 13 | 0.44 | 0.20 |
| I150034 | VTE-2510 | 1 1/2 NST | Red | 95 | 360 | 5.90 | 15 | 0.66 | 0.30 |
| I218950 | VTE-2510 | 1 1/2 NPSH | Red | 95 | 360 | 5.90 | 15 | 0.66 | 0.30 |
| I150015 | VTE-2510 | 1 1/2 NST | Black | 95 | 360 | 5.90 | 15 | 0.66 | 0.30 |