



OF10 Series

PVC/Nitrile Rubber Discharge Hose Assemblies

GENERAL APPLICATIONS

- Agriculture
- Cable covering
- Dewatering
- Drainage
- Floation booms
- Industrial washdown
- Irrigation
- Limited oil and chemical applications
- Pump discharge
- Watering

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/OF10ASL

CONSTRUCTION

Black PVC/Nitrile hose using an extruded through-the-weave process with circular woven high tenacity polyester reinforcement.

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

FEATURES AND ADVANTAGES

- **Factory Tested** – 100% pressure tested with factory certificate.
- **Complete Assembly** – Includes crimped on Sphere Lock™ male and female type B ball and socket couplings.
- **Proprietary PVC/Nitrile Material** – Specially developed PVC/Nitrile material provides superior abrasion, UV, chemical and oil resistance compared to PVC hoses.
- **Unique Woven Construction** – Specially designed weave pattern provides resistance to snaking, kinking, stretching and twisting.



A Kuriyama Group Company



FEATURING
SPHERE LOCK™
COUPLINGS

Part Number	Size		Wall Thickness (in)	Working Pressure (psi) at 68°F	Burst Pressure (psi) at 68°F	Coil Length (ft)	Tensile Strength (lbs)	Weight (lbs/pc)
	(in)	(mm)						
OF10ASL400X50	4	101.6	0.094	175	435	50	17,400	49.0
OF10ASL600X50	6	152.4	0.118	175	435	50	36,000	77.0
OF10ASL800X50	8	203.2	0.134	145	360	50	51,950	129.0

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.