


KC4-V59
KC4-V150
KC4-V159
KC4-V160

| | | | | |
|--|----------------|--------------|----------------|---------------|
| Crimping Force (ton) | 155 | 340 | 330 | 386 |
| Max. Capacity 1-2 Wire Braided (in) | 1 1/2 | 2 1/2 | 2 1/2 | 3 |
| Max. Capacity 4 Spiral (in) | 1 1/4 | 2 1/2 | 2 1/2 | 3 |
| Max. Capacity 6 Spiral (in) | 1 | 2 1/2 | 2 1/2 | 3 |
| Max. Capacity Industrial (in) | NA | 4 | 5* | 6 |
| Max. Opening without Dies (mm / in) | 119 / 4.69 | 189 / 7.44 | 228 / 8.98 | 288 / 11.34 |
| Max. Opening with Dies (mm / in) | 96 / 3.78 | 166 / 6.35 | 201 / 7.91 | 261 / 10.28 |
| Power | 7.5 HP (230 V) | 7 HP (230 V) | 7.5 HP (230 V) | 10 HP (230 V) |
| Page Number | 22-23 | 24, 27 | 25, 27 | 26-27 |

* up to 6" (depending on hose and coupling type)


KC4-V250
KC4-V300
KC4-V450

| | | | |
|--|---------------|---------------|---------------|
| Crimping Force (ton) | 551 | 725 | 728 |
| Max. Capacity 1-2 Wire Braided (in) | 3 | 3 | 3 |
| Max. Capacity 4 Spiral (in) | 3 | 3 | 3 |
| Max. Capacity 6 Spiral (in) | 3 | 3 | 3 |
| Max. Capacity Industrial (in) | 10 | 12 | 16 |
| Power | 15 HP (230 V) | 10 HP (230 V) | 10 HP (230 V) |
| Max. Opening without Dies (mm / in) | 380 / 14.96 | 475 / 18.70 | 560 / 22.05 |
| Max. Opening with Dies (mm / in) | 340 / 13.39 | 345 / 13.58 | 530 / 20.80 |
| Page Number | 28-29 | 30-31 | 32-33 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.