



T351LL / T351LG 150 PSI Premium Paper Mill/ Creamery Wash Down Hose With Tapered Nozzle

T351LL
White Cover

T351LG
Green Cover

3-A
COMPLIANT MATERIAL

General Applications:

For general wash down service, using hot and cold water in paper mills and in food and dairy plants.

Construction:

Tube: White EPDM. Meets FDA and 3A (18-03) requirements.

Reinforcement: High tensile textile cords.

Cover: White or green EPDM – heat, abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Service Temperature Range:

-40°F (-40°C) to +248°F (+120°C)

Standard Length:

50 feet including 6" long built-in tapered nozzle*

*Tapered Nozzle Hole Size

3/4" and 1" ID 3/8"
1 1/4" ID 1/2"
1 1/2" ID 5/8"

*T351 fully complies with the requirements listed in FDA CFR21.

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T351LL/LG075	3/4	19	1.22	31	150	50	0.44
T351LL/LG100	1	25	1.46	37	150	50	0.54
T351LL/LG125	1 1/4	32	1.81	46	150	50	0.78
T351LL/LG150	1 1/2	38	2.05	52	150	50	0.91

COUPLING SUGGESTIONS

Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.