



T452LE Series 150 PSI Potable Water Hose Hose is not NSF Approved

3-A
COMPLIANT MATERIAL

General Applications:

Discharge of water used for drinking. Most often used for temporary water lines in construction and industrial applications.

Construction:

Tube: White NR. Meets FDA and 3A (18-03) requirements.

Reinforcement: High tensile textile cords.

Cover: Blue SBR/EPDM blend – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T452 10 BAR POTABLE WATER HOSE (150 PSI) WP (in white letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T452LE150	1 1/2	38	1.97	50	150	100	0.73
T452LE200	2	51	2.56	65	150	100	1.13
T452LE300	3	76	3.62	92	150	100	1.88
T452LE400	4	102	4.65	118	150	100	2.51

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 36.

COUPLING SUGGESTIONS

Quick-Acting couplings attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.