



**T601AA Series**  
**150 PSI Oil Rigger/Oil Field-  
 Frack Tank Hose**

**General Applications:**

Oil field vacuum tank service, for handling crude oil, frack solutions and slurries.

**Note: For applications up to 35% aromatics. Not for use with refined petroleum products.**

**Construction:**

**Tube:** Black Nitrile – PVC blend, limited oil resistance, for oil field use.

**Reinforcement:** High tensile textile cords with flexible steel helix wire.

**Cover:** Black SBR – abrasion, ozone, limited oil resistance.

**Working Pressure:**

Constant Pressure – 10 Bar (150 PSI)

**Service Temperature Range:**

-22°F (-30°C) to +176°F (+80°C)

**Branding:**

ALFAGOMMA – ITALY T601 10 BAR (150 PSI) OIL FIELD-FRACK TANK HOSE (in blue letters)

**Nominal Specifications**

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
T601AA200	2	51	2.40	61	150	30	10	100	0.93
T601AA300	3	76	3.46	88	150	27	15	100	1.73
T601AA400	4	102	4.57	116	150	27	20	100	2.40
T601AA600	6	152	6.61	168	150	24	30	20/100	4.59

**COUPLING SUGGESTIONS**

Quick-Acting couplings or combination nipples attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.