

## 6C5AA Series 150 PSI Corrugated Tank Truck Hose

**NEW**

**CORRUGATED**



### General Applications:

For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content.

### Construction:

**Tube:** Black Conductive NBR.

**Reinforcement:** High tensile textile cords with flexible steel helix wire.

**Cover:** Black corrugated CR – abrasion, ozone, and hydrocarbon resistant.

### Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

### Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

### Branding:

ALFAGOMMA – ITALY T6C5 10 BAR (150 PSI)  
PETROLEUM TANK TRUCK (in red letters)

## Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
6C5AA200	2	51	2.48	63	150	30	4	100	0.85
6C5AA300	3	76	3.44	90	150	27	6	100	1.57
6C5AA400	4	102	4.57	116	150	27	8	100	2.21
6C5AA600	6	152	6.54	166	150	27	12	20	3.59

### COUPLING SUGGESTIONS

Quick-Acting couplings or combination nipples attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.