



T620AA Series 300 PSI Black Fuel & Oil S & D Hose

General Applications:

Fuel and oil suction and discharge for up to 50% aromatic content. Designed for heavy duty applications.

Construction:

Tube: Black conductive NBR.

Reinforcement: High tensile textile cords with steel helix wire and static wire.

Cover: Black conductive CR – abrasion, ozone and hydrocarbon resistant.

Working Pressure:

Constant Pressure – 20 Bar (300 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T620 – 20 BAR (300 PSI)
PETROLEUM – S & D Ω (in red letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
T620AA200	2	51	2.48	63	300	30	8	100	1.10
T620AA300	3	76	3.54	90	300	27	12	100	1.77
T620AA400	4	102	4.57	116	300	27	16	100	2.43
T620AA600	6	152	6.69	170	300	24	24	20/100	5.60
T620AA800	8	203	8.86	225	300	21	32	20	9.24

COUPLING SUGGESTIONS

Quick-Acting, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.