



## T650AH Series 150 PSI Oil Discharge Hose

### General Applications:

Oil discharge hose designed for use on trucks, docks or barges where a soft wall hose is required.

### Constructions:

**Tube:** Black conductive NBR.

**Reinforcement:** Spiraled high tensile textile cords with embedded static wire.

**Cover:** Red CR – abrasion, ozone and hydrocarbon resistant.

### Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

### Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

### Branding:

ALFAGOMMA – ITALY T650 10 BAR (150 PSI) – PETROLEUM DELIVERY (in yellow letters)

## Nominal Specifications

Series	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T650AH150	1 1/2	38	1.97	50	150	100	0.77
T650AH200	2	51	2.40	61	150	100	0.82
T650AH300	3	76	3.46	88	150	100	1.42
T650AH400	4	102	4.49	114	150	100	1.92

### COUPLING SUGGESTIONS

Quick-Acting or combination nipples attached with bands.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.