

T614AA Series 150 PSI Hot Tar & Asphalt S & D Hose



General Applications:

Hot tar and asphalt suction and discharge service.

Construction:

Tube: Black NBR – hot tar and asphalt resistant.

Reinforcement: High tensile textile cords with steel helix wire.

Cover: Black CSM – abrasion, ozone and hot tar resistant.

Working Pressure:

10 Bar (150 PSI)

Service Temperature Range:

-4°F (-20°C) to +356°F (+180°C)

Branding:

ALFAGOMMA – ITALY T614 10 BAR (150 PSI)
HOT TAR AND ASPHALT (on red stripe)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Wall Thickness (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius (in)	Standard Length (ft)	Weight (lbs/ft)
T614AA200	2	51	2.72	69	9	150	30	10	100	1.64
T614AA300	3	76	3.78	96	10	150	27	15	100	2.69
T614AA400	4	102	4.80	122	10	150	27	20	100	3.57

COUPLING SUGGESTIONS

Permanently attached couplings are suggested for assemblies.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.