



## T631AA Series 300 PSI Hot Tar & Asphalt Applicator Delivery Hose

**General Applications:**

Hot tar and asphalt delivery service.

**Construction:**

**Tube:** Black NBR – hot tar and asphalt resistant.

**Reinforcement:** High tensile steel wire braids.

**Cover:** Black CR – abrasion, ozone, hydrocarbon and fire resistant.

**Working Pressure:**

20 Bar (300 PSI)

**Service Temperature Range:**

-22°F (-30°C) to +356°F (+180°C)

**Branding:**

ALFAGOMMA – ITALY T631 20 BAR (300 PSI)  
HOT TAR AND ASPHALT (embossed)

**Safety Factor:**

10:1

### Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Wall Thickness (mm)	Max Rec. WP (psi)	Min. Bending Radius (in)	Standard Length (ft)	Weight (lbs/ft)
T631AA075	3/4	19	1.26	32	6	300	3	50/100	0.50
T631AA100	1	25	1.50	38	6	300	3	50/100	0.77

**COUPLING SUGGESTIONS**

Permanently attached couplings are suggested for assemblies.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.