

T757AA Series / T737AA Series

600 PSI Plaster & Concrete Hose

(Series T737AA for 3" ID)



General Applications:

Designed for pumping plaster, grout, and wet cement to placement sites.

Construction:

Tube: Black conductive NR – abrasion resistant.

Reinforcement: High tensile textile cords.

Cover: Black conductive SBR/NR – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 40 Bar (600 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T757 – 40 BAR (600 PSI)
PLASTER & CONCRETE (in white letters) and
ALFAGOMMA – ITALY T737 – 40 BAR (600 PSI)
PLASTER & CONCRETE (in white letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T757AA150	1 1/2	38	2.13	54	600	100	0.82
T757AA200	2	51	2.64	67	600	100	1.09
T737AA300	3	76	4.09	104	600	100	2.96

COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.