



T758AA / T758AE 800 PSI Plaster, Grout & Concrete Hose

T758AA
Black Cover

T758AE
Blue Cover

General Applications:

Designed for pumping plaster, grout, wet cement to construction placement sites at rated pressures.

Construction:

Tube: Black conductive NR – abrasion-resistant.

Reinforcement: Spiraled high tensile textile cords.

Cover: Black SBR/NR. Blue SBR/EPDM.

Working Pressure:

Constant Pressure – 55 Bar (800 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T758 – 55 BAR (800 PSI)
PLASTER & CONCRETE (in white letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T758AA/AE100	1	25	1.57	40	800	100	0.60
T758AA/AE125	1 1/4	32	1.93	49	800	100	0.85
T758AA/AE150	1 1/2	38	2.28	58	800	100	1.15
T758AA/AE200	2	51	2.80	71	800	100	1.49

COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.