

HWT763AA Series

75 PSI Heavy Duty Dry Powder Delivery Hose

3/8" Tube

NEW



General Applications:

Discharge of dry powders under low pressure. Pneumatic transfer of dry materials and abrasive slurries.

Construction:

Tube: 3/8" black static conducting NR – compounded to resist cutting by abrasive materials.

Reinforcement: Spiraled high tensile textile cords.

Cover: Black conductive SBR/NR blend – abrasion and ozone resistant.

Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T763 5 BAR (75 PSI)
HEAVY DUTY BULK MATERIAL DELIVERY (in green letters)

Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
HWT763AA400	4	102	4.96	126	75	100	2.56

★ Excessive bending during operation may cause premature wear.

COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.