


## T155AK Series 300 PSI Textile Cord “Air Drill” Hose



### General Applications:

High quality air hose for mining and construction service.

### Construction:

**Tube:** Black SBR/NBR blend – oil mist resistant.

**Reinforcement:** Spiraled, high tensile textile cords.

**Cover:** Yellow SBR – abrasion and ozone-resistant.

### Working Pressure:

Constant Pressure – 20 Bar (300 PSI)

### Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

### Branding:

ALFAGOMMA – ITALY – T155 20 BAR (300 PSI)  
AIR (in blue letters)

## Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Standard Length (ft)	Weight (lbs/ft)
T155AK050	1/2	13	0.83	21	300	50/100	0.22
T155AK075	3/4	19	1.14	29	300	100	0.38
T155AK100	1	25	1.38	35	300	50/100	0.48
T155AK125	1 1/4	32	1.73	44	300	100	0.60
T155AK150	1 1/2	38	1.97	50	300	100	0.70
T155AK200	2	51	2.56	65	300	50/100	1.12
T155AK250	2 1/2	63	3.11	79	300	50/100	1.55
T155AK300	3	76	3.62	92	300	50/100	1.89
T155AK400	4	102	4.65	118	300	50/100	2.47

### COUPLING SUGGESTIONS

Steel or malleable iron male insert NPT, female ground joint or washer type with spud, attached with 2 or 4 bolt interlocking clamps or bands. Universal couplings may be used on sizes (1/2" – 2")

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.