



## T204AA Series 75 PSI SBR Water S & D Hose

### General Applications:

Suction and discharge of water for irrigation and construction.

### Construction:

**Tube:** Black SBR.

**Reinforcement:** Spiraled high tensile textile cords with flexible steel helix wire.

**Cover:** Black SBR – ozone and abrasion-resistant.

### Working Pressure:

Constant Pressure – 5 Bar (75 PSI)

### Service Temperature Range:

-22°F (-30°C) to +176°F (+80°C)

### Branding:

ALFAGOMMA– ITALY – T204 (embossed)

## Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max Rec. WP (psi)	Vacuum HG (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
T204AA600	6	152	6.54	166	75	24	30	20/25/50/100	4.13
T204AA800	8	203	8.70	221	75	21	40	20/25	7.06

### COUPLING SUGGESTIONS

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

★ Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type and pricing.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.