



## Gaskets



**White Neoprene (FDA) Gasket for Quick-Acting Couplings**

Temperature Rating -45°F (-43°C) to 250°F (+121°C)

Part Number	Size (in.)	Weight Each (lbs.)	Standard Carton
WN100	1	0.010	10
WN200	2	0.022	10
WN300	3	0.042	10
WN400	4	0.066	10
WN500	5	0.094	10
WN600	6	0.116	10

Note: Sold in standard carton quantity only.



**BUNA-N Shank Band for EZ-Seal™ Leak Resistant Couplings**

Temperature Rating -40°F (-40°C) to 250°F (+121°C)

Part Number	Size (in.)	Weight Each (lbs.)	Standard Carton
NBR-LF150	1 1/2	0.004	10
NBR-LF200	2	0.009	10
NBR-LF300	3	0.029	10
NBR-LF400	4	0.040	10

Note: Sold in standard carton quantity only.



**EPDM Gasket for Irri-Loc® Couplings**

Temperature Rating -40°F (-40°C) to 180°F (+82°C)

Part Number	Size (in.)	Weight Each (lbs.)	Standard Carton
IL-J200	2	0.040	40
IL-J300	3	0.130	40
IL-J400	4	0.220	30
IL-J600	6	0.530	10
IL-J800	8	0.660	10



**BUNA-N Gasket for API Petroleum Couplings**

Temperature Rating -40°F (-40°C) to 250°F (+121°C)

Part Number	Size (in.)	Weight Each (lbs.)	Standard Carton
TCG-400	4	0.070	1

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.