NFORMATION

TR5TT - R5 Temp Tech One Wire Braid

One-wire Braid Hydraulic Hose – TR5TT



TR5TT – One wire braid - Reinforced Meets or exceeds SAE 100 R5

General Applications:

Medium pressure service hydraulic petroleumbased oil line in impulse applications; lube oil, diesel fuel lines and oil for Bio-diesel; applications such as air brakes, power steering, turbocharger oil supplies, tilt cab cylinders, transmission coolant, engine coolant and filtration lines. Meets or exceeds requirements of SAE 100 R5 for traditional hydraulic applications.

Construction:

Tube – Oil-resistant synthetic rubber. **Reinforcement –** One high tensile steel braid. **Cover –** Polyester textile braid. Specially designed for high temperature applications.

Temperature Range:

-40°F (-40°C) to +300°F (+150°C) constant operation.

Air max T up to 5/8" = +85°C (+185°F) Air max T over 3/4" = +110°C (+230°F)

Branding:

ALFAGOMMA FLEXOR 5 ID ...WP ...MPa (...PSI) SAE 100 R5

Nominal Specifications											
Series Number	Size Code	ID		OD		Max.	Min. Bend. Radius			Coupling Recommendations	
						Working [†] Pressure (psi)			Weight (Ibs/ft)	Two-Piece	
		(in)	(mm)	(in)	(mm)		(in)	(mm)		Ferrule Non-Skive	Insert Non-Skive
TR5TT	04	3/16	4.8	0.52	13.2	3000	3.0	76.2	0.16	AFX-03	A-03XX
TR5TT	05	1/4	6.4	0.58	14.8	3000	3.4	86.4	0.19	AFX-04	A-04XX
TR5TT	06	5/16	7.9	0.68	17.3	2250	4.0	101.6	0.24	AFX-05	A-05XX
TR5TT	80	13/32	10.3	0.77	19.5	2000	4.6	116.8	0.28	AFX-06	A-06XX
TR5TT	10	1/2	12.7	0.92	23.4	1750	5.5	139.7	0.38	AFX-08	A-08XX
TR5TT	12	5/8	15.9	1.08	27.4	1500	6.5	165.1	0.46	AFX-10	A-10XX
TR5TT	16	7/8	22.2	1.24	31.4	800	7.3	185.4	0.47	AFX-12	A-14XX
TR5TT	20	1 1/8	28.6	1.50	38.1	625	9.0	228.6	0.58	AFX-16	A-18XX
TR5TT	24	1 3/8	34.9	1.75	44.5	500	10.5	266.7	0.72	AFX-20	A-22XX
TR5TT	32	1 13/16	46.0	2.22	56.4	350	13.2	335.3	0.91	AFX-32	A-29XX

† Minimum burst pressure 4-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.