
PFP354 PLUS 100R7

PFP354 Series

H Y D R A U L I C S

Abrasion Resistant / Special Low Friction Polyurethane Cover









General Applications:

Piranhaflex[™] **Plus PFP354** Series is the ideal hose for medium pressure hydraulic lines commonly used on Fork Trucks. The "**Plus**" refers to the specially engineered low friction cover compound which helps in eliminating hose routing problems between hose sheaves and pulleys. Use of Piranhaflex[™] **Plus** helps in extending hose service life with less frequent replacement and allows for increased flexibility and easier routing when hoses are bundled.

(-12 and -16 MTO are available upon request)

Construction:

Piranhaflex[™] **PLUS PFP354** Series consists of three individual components bonded to ensure maximum performance.

Tube – Seamless nylon inner tube.

Reinforcement – Braided high tensile strength fiber reinforcement.

Cover – PFP354 Series has a black abrasion resistant / special low friction polyurethane pin pricked cover.

Service Temperature Range:

-40°F (-40°C) to +200°F (+93°C) for petroleum based hydraulic fluids.

Features & Advantages:

- Meets or exceeds SAE J517 Standards.
- Tested at ½ bend radius under SAE Standards.
- Exceeds 100R7 impulse requirements
- Light weight and flexible.
- Special low friction cover eliminates hose routing problems between hose sheaves and pulleys with Fork Truck applications.

Packaging:

Hoses supplied in 250 ft. reels.

www.kuriyama.com

- All reels will have no more than 2 pieces, with no piece less than 50' in length.
- All specials are treated as a made-to-order item and will require a minimum of 5,000 ft. to produce.

Nominal Specifications

Series Number	Size Code	ID		OD		Max.	Min. Bend. Radius			Coupling Recommendations
		(in)	(mm)	(in)	(mm)	Working [†] Pressure (psi)	(in)	(mm)	Weight (lbs/ft)	Two-Piece
										Ferrule Non-Skive
PFP354	04	1/4	6.4	0.496	12.6	2750	1.50	38.1	0.06	PFR-04
PFP354	06	3/8	9.7	0.650	16.5	2250	2.00	50.8	0.11	PFR-06
PFP354	08	1/2	13.1	0.834	21.2	2000	3.00	76.2	0.16	PFR-08

[†] Minimum burst pressure 4-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.