

WB10 - Waterblast MINETUFF



Waterblast Hose WB 10

NEW

**WB10 –
4 wire spiral**



General Applications:

High pressure water jetting

Construction:

Tube – Oil and water resistant synthetic rubber.
Reinforcement – Four high tensile steel spirals.
Cover – Oil, water and ozone resistant synthetic rubber.

Service Temperature Range:

Constant operation: +14°F (-10°C) to +158°F (+70°C)

Branding:

Dunlop Hiflex

Length:

Random length coils, all in multiples of 50 feet.
 Examples: 200', 250', 300', 350'

Nominal Specifications

Series Number	Size Code	ID		OD		Max Working Pressure (psi)	Min. Bend. Radius		Weight (lbs/ft)	Coupling Recommendations	
		(in)	(mm)	(in)	(mm)		(in)	(mm)		Two-Piece	
										Ferrule Skive	Ferrule Interlock
WB10	06	3/8	9.5	0.79	20.1	10000	6.0	152.4	0.37	AS4	
WB10	08	1/2	12.7	0.97	24.6	10000	8.0	203.2	0.54		XF2
WB10	12	3/4	19.1	1.24	31.4	10000	8.2	208.3	0.99		XF2
WB10	16	1	25.4	1.51	38.2	10000	11.0	279.4	1.37		XF2

† Minimum burst pressure: 2.5-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



HOSES
 ONE-PIECE B SERIES
 ONE-PIECE D SERIES
 ONE-PIECE F & P SERIES
 TWO-PIECE FERRULES (A & PFR SERIES)
 TWO-PIECE INSERTS (A SERIES)
 TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)
 QUICK RELEASE
 ASSEMBLY EQUIPMENT
 TECHNICAL INFORMATION