

Farm Tank Bulk Hose & Coupled Assemblies

General Applications:

- Agricultural equipment fuel filler hose
- Electrical pumps; built-in static wire provides safety
- Farm or barrel-type pumps
- Fuel dispensing hose for construction and industrial equipment

Note: This is not a UL approved hose and should not be used in curb pump hose applications.

Construction:

- **Tube** – Black Class A Nitrile, high oil resistance.
- **Reinforcement** – Polyester cord with static wire.
- **Cover** – Black Class A Nitrile /PVC, high oil resistance.

Service Temperature Range:

-20°F (-29°C) to +160°F (+70°C)

Features and Advantages:

- A durable quality fuel dispensing hose - oil & abrasion resistant.

Branding:

REDI-FILL™ FARM TANK W/STATIC WIRE- SIZE- MADE IN USA

Packaging:

Brass M X M coupled assembled lengths and reels (2 pcs maximum).

Note: 3/4" assemblies packaged 10 per carton; 1" assemblies packaged 5 per carton; or sold individually.



Redi-Fill™ Coupled Assemblies

Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Coil Length (ft)	Weight (lbs/pc)
BLKFT-075X8	Black	3/4	1.13	60	8	3.3
BLKFT-075X10	Black	3/4	1.13	60	10	3.8
BLKFT-075X12	Black	3/4	1.13	60	12	4.0
BLKFT-075X14	Black	3/4	1.13	60	14	5.0
BLKFT-075X15	Black	3/4	1.13	60	15	5.4
BLKFT-075X20	Black	3/4	1.13	60	20	7.0
BLKFT-100X8	Black	1	1.38	60	8	4.8
BLKFT-100X10	Black	1	1.38	60	10	5.8
BLKFT-100X12	Black	1	1.38	60	12	6.7
BLKFT-100X14	Black	1	1.38	60	14	7.5
BLKFT-100X15	Black	1	1.38	60	15	8.0
BLKFT-100X20	Black	1	1.38	60	20	10.5

Redi-Fill™ Bulk Hose on Reels

Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
BLKFT-075X700	Black	3/4	1.13	60	700	203
BLKFT-100X700	Black	1	1.38	60	700	315

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.