



250 PSI Push-On Hose

General Applications:

- Air tools
- Hot and cold water
- Low pressure pneumatic systems
- Water, oil and mild chemical solutions
- ★ Not recommended for unleaded gasoline

Construction:

- **Tube** - Black Nitrile, RMA Class A oil resistant.
- **Reinforcement** - Aramid spiral yarn.
- **Cover** - Red or blue Nitrile/PVC, RMA Class A oil resistant.

Service Temperature Range:

-20°F (-29°C) to +180°F (+82°C)

Features and Advantages:

- Easy to couple.
- Long lengths on reels.

Branding:

REDI-LOCK 250 PSI <size> MADE IN USA

Packaging:

Hoses supplied on plastic reels; maximum 2 pcs. on reel.

Note: For Push-On Fittings and Quick Disconnect Couplings refer to pages 15-17 of this catalog.



Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
REDI-RED-04X700	Red	1/4	0.50	250	700	63
REDI-RED-06X700	Red	3/8	0.63	250	700	84
REDI-RED-08X700	Red	1/2	0.75	250	700	112
REDI-BLU-04X700	Blue	1/4	0.50	250	700	63
REDI-BLU-06X700	Blue	3/8	0.63	250	700	84
REDI-BLU-08X700	Blue	1/2	0.75	250	700	112

Note: Cut lengths for this product are available from our Kuriyama Schaumburg, IL Warehouse location. Please call (847) 755-0360 or e-mail: sales@kuriyama.com for more information.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.