



BLACK CLOTH-INSERTED SBR SHEET

General Properties of SBR†

- Excellent physical properties.

† Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

SPECIFICATIONS:

Commercial grade black SBR sheet, with cloth reinforcement:

Style CI: 60 Duro hardness (Shore Durometer A)

Common Name: Cloth-reinforced Black Rubber Sheet

Polymer: Styrene-Butadiene Rubber reinforced with 3.4 oz./sq. yd. nylon fabric

ISO/ASTM Designation: SBR

Talc Free

Style	ASTM Specification (SI units)	Temp. Range	Ply	Durometer	Tensile Strength (psi)	Elongation (%)	Finish
CI	D 2000 M2AA 603 A13 B13 EA14	-20°F to +170°F	1	55 – 65	435	250%	Plate
CI	D 2000 M2AA 603 A13 B13 EA14	-20°F to +170°F	2	55 – 65	435	250%	Plate
CI	D 2000 M2AA 603 A13 B13 EA14	-20°F to +170°F	3	55 – 65	435	250%	Plate
CI	D 2000 M2AA 603 A13 B13 EA14	-20°F to +170°F	4	55 – 65	435	250%	Plate

ORDERING INFORMATION:

Part Number	Gauge x Width (in)	Fabric Plies	Avg. Length (Linear ft /Roll)	Approx. lbs/Roll
CI-1P02x48x67	1/16 x 48	1 Ply	67	132
CI-2P04x48x36	1/8 x 48	2 Ply	36	140
CI-2P04x48x50	1/8 x 48	2 Ply	50	194
CI-2P06x48x18	3/16 x 48	2 Ply	18	107
CI-2P06x48x50	3/16 x 48	2 Ply	50	297
CI-2P08x48x18	1/4 x 48	2 Ply	18	140
CI-2P08x48x25	1/4 x 48	2 Ply	25	194
CI-2P08x48x50	1/4 x 48	2 Ply	50	388
CI-3P06x48x18	3/16 x 48	3 Ply	18	107
CI-4P08x48x18	1/4 x 48	4 Ply	18	140

BLACK SBR SHEET

General Properties of SBR†

- Good physical properties.

† Properties shown based on Rubber Manufacturers Association Sheet Rubber Handbook, second edition.

SPECIFICATIONS:

Commercial grade black SBR sheet:

Style BL60: 65 Duro hardness (Shore Durometer A)

Common Name: Black Rubber Sheet

Polymer: Styrene-Butadiene

ISO/ASTM Designation: SBR

Talc Free

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (psi)	Elongation (%)	Finish
BL60	D 2000 M1AA 604	-13°F to +158°F	60 – 70	600	200%	Plate

ORDERING INFORMATION:

Part Number	Gauge x Width (in)	Avg. Length (Linear ft/Roll)	Approx. lbs/Roll
BL60-02x48x50	1/16 x 48	50	98
BL60-04x48x50	1/8 x 48	50	194
BL60-08x48x25	1/4 x 48	25	194