



**KURIYAMA**  
INDUSTRIAL RUBBER HOSE

# **King Bee**™

by KURIYAMA

## **Liquid Suction and Wastewater Hose**

*Highly Flexible – great  
for portable toilets*

*Crush Resistant*

*Wear Resistant*



**KBEE™ Series**



**KURIYAMA**  
OF AMERICA, INC.



EDITION 1019

# KBEE™ Series

## Polyethylene Hose Guard



### General Applications:

- Protection of high pressure sewer jetting hoses

### Construction:

Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends.

### Service Temperature Range:

-40°F (-40°C) to +150°F (+65°C)\*

### Features and Advantages:

- **Easy Slide Interior** – low coefficient of friction polyethylene tube allows for sewer jetting hoses to slide through easily, protecting them from wear.
- **“Cold-Flex” Materials** – Remains flexible in sub-zero temperatures.
- **Crush Resistant** – Will spring back to original shape after being crushed, will not kink!
- **Easy Slide Helix** – Exposed ribs protect tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.
- **Leak Proof Cuffs** – Overmolded cuffs will not separate from the hose guard. Each cuff and unit is 100% factory tested.



### King Bee™ Collar Clamp with 20' Rope

- Available in plated steel or corrosion resistant stainless steel

Part Number	ID (in)	Material	Weight (lbs)
KBC-CS300	3	Plated	0.64
KBC300	3	Stainless	0.67



(Hose sold separately)

### Nominal Specifications

Part Number	ID		OD		Working Pressure at 68°F (psi)	Vacuum Rating Hg at 68°F (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
KBEE2X3	2	50.8	2.76	70.1	15	29	3.5	3	2.55
KBEE3X3	3	76.2	4.06	103.1	7	29	6.5	3	4.80

**NOTE:** Service life may vary depending on operating conditions and type of material being conveyed.  
\*Actual service temperature range is application dependent.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.