13

Kuri Tec®

2840, 2841, 2844, 2846 Series

95 Shore "A" Ether-Based Heavy Duty Polyurethane Tubing



Ether-based polyurethane tubing available in colors for transfer of air, fluids and abrasive slurries.

Construction:

Series 2840, 2841, 2844, 2846 — 95 Shore "A" Durometer ether-based polyurethane tubing in FDA⁽⁰⁷⁾ and NSF⁽⁰⁹⁾ clear material, 2840 – Clear, as well as three industrial grade solid colors: 2841 – Yellow, 2844 – Red, 2846 – Blue

Features:

- Abrasion and cut resistance.
- Good flex fatigue and resilience characteristics.
- Excellent resistance to ozone, solvents and fuel.
- Good resistance to hydrolysis.
- Clear tubing* allows see-through convenience.
- Complies with RMA's Class A designation for high oil resistance.
- Silicone-free.

KKTCA0723

One-piece lengths.

- Individually bagged self store assemblies are available, see page 38.
- RoHS⁽¹⁶⁾ compliant.
- Phthalate Free!

Applications:

- Transfer of air and fluids under severe conditions.
- Feed and return lines.
- Abrasive slurry transfer.
- Granular transfer lines.
- Robotics control lines.
- Insulating sleeves.
- Lubrication lines.
- Metering pumps.

Note: Not recommended for transfer of brake fluids.

Service Temperature Range: -40°F (-40°C) to +175°F (+80°C)

Nominal Specifications Max. Working Approx. Wt. **Standard Lengths Nominal ID Nominal OD Series No-**Pressure† (PSI) per Pkg. Size @ 122°F @ 70°F 2841 2844 2846 Code 2840 Spool/Box Coil/Box (In) (In) 300 ft. | 100 ft. (mm) (mm) (20°C) (50°C) B' Tint | Yellow Red Blue 1/4 6.5 .375 9.5 125 75 300 ft. 100 ft. 9.5 lbs. 3.1 lbs. 04 21.7 lbs. 7.2 lbs. 06 3/8 9.5 .570 14.5 125 75 300 ft. 100 ft.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

FDA⁽⁰⁷⁾, NSF⁽⁰⁹⁾, PHTHALATE FREE⁽¹⁵⁾, RoHS⁽¹⁶⁾

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

[†] Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

^{*} Note: The Clear Series 2840 material conforms to the same FDA regulations as Series 2600.