Mill Discharge Assemblies





DJ Series

Double Jacket "Contractor Grade"Coupled with Male and Female
Aluminum Rocker Lug Couplings

General Applications:

- Heavy duty equipment or pump rental
- Hydrant-to-truck water supply line
- Municipal washdown
- Ship deck washdown

Construction:

Double jacket with 100% polyester yarn. Water and mildew-resistant cover, will not rot, even if the hose is stored wet.

Service Temperature Range:

-25°F (-31°C) to +185°F (+85°C)

Features & Advantages:

- Versatile Natural Rubber Tube Exhibits a good combination of strength and extreme flexibility for ease-of-use.
- Wide Service Temperature Range Hose may be used in a wide range of service temperature ranges from -25°F to +185°F.
- Double Jacket Double jacket provides additional external abrasion resistance.
- Compact Design Flat hose design rolls up into tight coils for easy storage and transport, takes up less space than other hoses.
- Storage/Shipping Carton Hoses are individually packaged in cartons for ease of handling and shipping.

| Nominal Specifications | | | | | | |
|------------------------|-------|------|--------|-------------|---------------------------|-------------|
| Part | Size | | Length | Throad Tuno | Max. Working | Weight Each |
| Number | (in) | (mm) | (fť) | Thread Type | Pressure (psi) at 68°F | (lbs) |
| DJ150NSTX50 | 1 1/2 | 38.1 | 50 | NST | 200 | 14 |
| DJ150NPSHX50 | 1 1/2 | 38.1 | 50 | NPSH | 200 | 14 |
| DJ250NSTX50 | 2 1/2 | 63.5 | 50 | NST | 200 | 23 |
| DJ250NPSHX50 | 2 1/2 | 63.5 | 50 | NPSH | 200 | 23 |