

# KURIYAMA Oil & Gas Products

## **Commercial Diving**

### "Pneumo" Hose K1166 Series **Low Pressure Air Hose**

The Pneumo fathometer system or "Pneumo" is usually contained in the commercial diver's air manifold box. It uses a small volume of low pressure air to measure the diver's depth.

Our high-quality PVC compounds enable this hose to perform extremely well as a low-pressure air hose versus standard rubber hoses. Its light weight makes it an ideal hose for Pneumo applications.



#### Construction:

- Tube White general purpose PVC compound.
- Reinforcement Spiralled high tensile synthetic yarn.
- Cover Bright blue general purpose PVC compound.

#### **Applications:**

- Diver's Pneumo hose used singly or with umbilicals
- General air supply line for pneumatic tools

#### **Features and Advantages:**

- Chemical resistance of PVC
- Compatible with brass re-usable fittings
- Extremely flexible and durable
- Lightweight
- Long continuous lengths
- Medium/high oil resistance, complies with RMA's Class B Designation
- Multiple colors to choose from
- Non-marking pin-pricked cover
- One-piece reel lengths
- Private branding available
- RoHS compliant
- Silicone-free core and cover
- U. V. and weather resistant

Service Temperature Range: -10°F (-23°C) to +150°F (+65°C)

#### **Nominal Specifications Max. Working** Approx. Weight **Nominal ID Nominal OD Standard Stock Color Standard Lengths** Pressure† (PSI) per Pkg. Size Code @70°F @122°F **K1166 Blue** (In) (mm) (In) Reel Reel (mm) (20°C) (50°C) 1/4 6.5 .500 300 2,500 ft. 255 lbs. 12.7

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.



### **Cautionary Statement**

All Products sold and distributed by Kuriyama of America, Inc. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Kuriyama of America, Inc. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

### **Limited Warranty**

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANUFACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

### Distributed by:



Since 1968

#### **HEADQUARTERS, SALES OFFICE AND WAREHOUSE**

360 E. State Parkway, Schaumburg, IL 60173-5335 Phone: (847) 755-0360 • Toll-free Fax: (800) 800-0320 International Fax: (847) 885-0996



















## CONTACT OUR SALES/WAREHOUSE LOCATIONS BELOW WHICH SERVE YOUR AREA

#### **SOUTHWEST WAREHOUSE**

KURIYAMA OF AMERICA, INC. – HOUSTON

200 Portwall Street, Suite 100
HOUSTON, TX 77029
Phone: (713) 674-8212
Toll Free Phone: (800) 501-6808
FAX: (713) 674-5214
Toll Free FAX: (800) 800-5214
E-Mail: sales@kuriyama.com

#### **WESTERN WAREHOUSE**

KURIYAMA OF AMERICA, INC.
– SANTA FE SPRINGS
10749 SHOEMAKER AVENUE
SANTA FE SPRINGS, CA 90670-4039
Phone: (562) 941-4507
FAX: (562) 941-8940
Toll-Free FAX: (800) 326-8940
E-Mail: sales@kuriyama.com

#### **SOUTHEAST WAREHOUSE**

FORTNEY SALES CO., INC. 4221 Cantrell Road NW Acworth, GA 30101
Phone: (770) 427-6528
FAX: (770) 423-9249
Toll Free FAX: (800) 423-9249
Web Site: www.fortneysales.com
E-Mail: sales@fortneysales.com

#### **EASTERN WAREHOUSE**

EASTERN RUBBER & PLASTICS CO., INC.
100 GOLDMAN DR.
PLUMSTED INDUSTRIAL PARK
CREAM RIDGE, NJ 08514
Phone: (609) 758-0100
FAX: (609) 758-0102
Toll Free FAX: (800) 445-7138
Web Site: www.easternrubber.com
E-Mail: sales@easternrubber.com

#### **IN MEXICO:**

KURIYAMA DE MÉXICO S DE RL DE CV AV JOSE PALOMO MARTINEZ NO 520-20 BODEGA 5 PARQUE INDUSTRIAL OMOLAP APODACA, N.L. CP:66633, MÉXICO Telefonos: (81) 1086-1870 0 71 Internet: www.kuriyama.com.mx www.kuriyama.com

Correo Electronico: ventas@kuriyama.com

The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.