

**Pressure Testing** - All Piranha Sewer Hoses are 100% pressure tested.

### General Applications:

- **High Pressure Sewer Cleaning** - Applications for commercial, industrial and residential.
- **Tight Pipe Bends** - Slick, Slither® cover affords an easier handling hose to get the job done.

### Construction:

- **Inner Tube** - Yellow seamless thermoplastic tube. (Sewer Cleaning Hoses: 2,500 PSI, 3,000 PSI, 4,000 PSI & 5,000 PSI)
- **Reinforcement** - High tensile one or two synthetic fiber braids.
- **Cover** - Polyurethane abrasion resistant. (Standard)



### Temperature:

- **Service Temperature Range** - See individual hose specifications for temperature ratings.

### Features & Advantages:

- **Materials** - Constructed to provide rugged and reliable service under the most severe and demanding conditions.
- **Yellow Color Tube** - Assures the user that they are using a WASTEC designated Piranha Hose Product.
- **Polyolefin or Seamless Thermoplastic Tube** - Provides maximum resistance to hydrolysis.
- **High Tensile One or Two Synthetic Fiber Braids** - Contributes to low volumetric expansion and eliminates loss of strength from moisture absorption.
- **Abrasion Resistant Polyurethane** - Polyurethane cover provides exceptional cut, abrasion and fungus resistance.
- **Slither® Cover** - Cover is ultra slippery; allows hose to maneuver around and through difficult sewer bends.
- **End Fittings** - Hoses are assembled Male X Male NPT threads as a standard, but other thread configurations are available.
- **Slither®** - Polyurethane-low coefficient of friction. (Optional)



### Industry Standards:

- **Orange Cover** = 2,500 PSI
- **Blue Cover** = 3,000 PSI
- **Green Cover** = 4,000 PSI
- **Black Cover** = 4,000 PSI (High Burst)

### Lengths:

- **Standard Lengths** - Continually leading to create, establish and stock industry standard lengths.
- **Custom Lengths** - Available and made to order.



# Sewer Cleaning Hoses



## 2,500 PSI SPOR Series



A yellow polyolefin tube, single high tensile synthetic fiber braid reinforcement and abrasion resistant orange polyether-urethane cover.

### Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SPOR-10	5/8	16.0	0.96	24.4	2500	172.4	6250	430.9	4.00	101.6	0.19
SPOR-12	3/4	19.1	1.18	30.0	2500	172.4	6250	430.9	5.00	127.0	0.28
SPOR-16	1	25.4	1.46	37.1	2500	172.4	6250	430.9	6.00	152.4	0.40
SPOR-20	1 1/4	32.0	1.80	45.7	2500	172.4	6250	430.9	8.00	203.2	0.59
SPOR-24	1 1/2	38.1	2.18	55.4	2500	172.4	6250	430.9	15.00	381.0	0.94



## 3,000 PSI HPBU Series



A yellow polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant blue polyether-urethane cover.

### Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
HPBU-12	3/4	19.1	1.18	30.0	3000	206.8	7500	517.1	5.00	127.0	0.29
HPBU-16	1	25.4	1.48	37.6	3000	206.8	7500	517.1	8.00	203.2	0.41
HPBU-20	1 1/4	31.2	1.80	45.7	3000	206.8	7500	517.1	10.00	234.0	0.59

# Jetting Line Hoses



## 4,000 PSI LLGR Series



A yellow seamless polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant green polyether-urethane cover.

### Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
LLGR-12	3/4	19.1	1.30	33.0	4000	275.8	10000	689.5	5.00	127.0	0.41
LLGR-16	1	25.4	1.63	41.4	4000	275.8	10000	689.5	8.00	152.4	0.65

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.