

**Pressure Testing** - All Piranha Sewer Hoses are 100% pressure tested.

### General Applications:

- **High Pressure Sewer Cleaning** - Applications for commercial, industrial and residential.
- **Tight Pipe Bends** - Slick, Slither® cover affords an easier handling hose to get the job done.

### Construction:

- **Inner Tube** - Yellow seamless thermoplastic tube. (Sewer Cleaning Hoses: 2,500 PSI, 3,000 PSI, 4,000 PSI & 5,000 PSI)
- **Reinforcement** - High tensile one or two synthetic fiber braids.
- **Cover** - Polyurethane abrasion resistant. (Standard)



### Temperature:

- **Service Temperature Range** - See individual hose specifications for temperature ratings.

### Features & Advantages:

- **Materials** - Constructed to provide rugged and reliable service under the most severe and demanding conditions.
- **Yellow Color Tube** - Assures the user that they are using a WASTEC designated Piranha Hose Product.
- **Polyolefin or Seamless Thermoplastic Tube** - Provides maximum resistance to hydrolysis.
- **High Tensile One or Two Synthetic Fiber Braids** - Contributes to low volumetric expansion and eliminates loss of strength from moisture absorption.
- **Abrasion Resistant Polyurethane** - Polyurethane cover provides exceptional cut, abrasion and fungus resistance.
- **Slither® Cover** - Cover is ultra slippery; allows hose to maneuver around and through difficult sewer bends.
- **End Fittings** - Hoses are assembled Male X Male NPT threads as a standard, but other thread configurations are available.
- **Slither®** - Polyurethane-low coefficient of friction. (Optional)



### Industry Standards:

- **Orange Cover** = 2,500 PSI
- **Blue Cover** = 3,000 PSI
- **Green Cover** = 4,000 PSI
- **Black Cover** = 4,000 PSI (High Burst)

### Lengths:

- **Standard Lengths** - Continually leading to create, establish and stock industry standard lengths.
- **Custom Lengths** - Available and made to order.





# Slither® Sewer Cleaning Hoses



## SLITHER® 2,500 PSI

### SLSPOR Series



A yellow polyolefin tube, single high tensile synthetic fiber braid reinforcement and abrasion resistant slick orange polyether-urethane cover.

### Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLSPOR-10	5/8	16.0	0.96	24.4	2500	172.4	6250	430.9	4.00	101.6	0.19
SLSPOR-12	3/4	19.1	1.18	30.0	2500	172.4	6250	430.9	5.00	127.0	0.28
SLSPOR-16	1	25.4	1.46	37.1	2500	172.4	6250	430.9	6.00	152.4	0.40
SLSPOR-20	1 1/4	32.0	1.80	45.7	2500	172.4	6250	430.9	8.00	203.2	0.59
SLSPOR-24	1 1/2	38.1	2.18	55.4	2500	172.4	6250	430.9	15.00	381.0	0.94



## SLITHER® 3,000 PSI

### SLHPBU Series



A yellow polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant slick blue polyether-urethane cover.

### Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLHPBU-12	3/4	19.1	1.18	30.0	3000	206.8	7500	517.1	5.00	127.0	0.29
SLHPBU-16	1	25.4	1.48	37.6	3000	206.8	7500	517.1	8.00	203.2	0.41
SLHPBU-20	1 1/4	31.2	1.80	45.7	3000	206.8	7500	517.1	10.00	234.0	0.59



# Slither® Jetting Line Hoses



## SLITHER® 4,000 PSI

### SLGR Series



A yellow seamless polyolefin tube, double high tensile synthetic fiber braid reinforcement and abrasion resistant slick green polyether-urethane cover.

### Nominal Specifications

Service Temperature Range: -40°F (-40°C) to +150°F (+66°C)

Series Number	ID		OD		Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius		Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	(psi)	(bar)	(psi)	(bar)	(in)	(mm)	
SLGR-12	3/4	19.1	1.30	33.0	4000	275.8	10000	689.5	5.00	127.0	0.41
SLGR-16	1	25.4	1.63	41.4	4000	275.8	10000	689.5	8.00	152.4	0.65

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



Kuriyama of America, Inc.

www.kuriyama.com