



FT™ Series

Heavy Duty Food Grade PVC Suction Hose

General Applications:

- Food grade liquids such as milk, beer, wine and juice
- Food grade material handling – standard duty
- Ice transfer
- Milk and dairy product transfer
- Poultry processing
- Water suction – heavy duty

Construction: PVC tube with rigid PVC helix.

Service Temperature Range:

-4°F (-20°C) to +150°F (+65°C)*

Features and Advantages:

- **Food Grade Materials** – Hose complies with applicable FDA⁽⁰³⁾ and 3-A⁽⁰¹⁾ requirements. Hose complies with applicable USDA⁽¹²⁾ requirements.
- **Transparent Construction** – “See-the-flow.” Allows for visual confirmation of material flow.
- **Smooth Outer Cover** – Provides increased pressure rating and smooth surface for banding.
- **Phthalate Free**

Nominal Specifications											
Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
FT075	3/4	19.0	0.94	24.0	115	75	Full	28	3	100	0.17
FT100	1	25.5	1.28	32.5	100	70	Full	28	3	100	0.24
FT125	1-1/4	32.0	1.56	39.6	90	65	Full	28	4	100	0.44
FT150	1-1/2	38.1	1.80	46.5	85	60	Full	28	6	100	0.50
FT200	2	50.8	2.36	60.0	85	60	Full	26	8	100	0.71
FT250	2-1/2	63.5	2.88	73.2	65	45	Full	26	10	100	0.94
FT300	3	76.2	3.42	86.9	55	40	Full	24	11	100	1.14
FT400	4	101.6	4.51	114.6	50	35	Full	24	18	100/60	1.91
FT500	5	127.0	5.51	140.0	40	25	28	23	28	100/20	2.41
FT600	6	153.4	6.59	167.4	30	20	28	15	48	20	3.28
FT800	8	204.7	8.85	224.7	25	15	28	10	60	20	5.67

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.

3A⁽⁰¹⁾, BSE/TSE⁽⁰²⁾, FDA⁽⁰³⁾, PHTHALATE FREE⁽¹⁰⁾, RoHS⁽¹¹⁾, USDA⁽¹²⁾

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

