



ABRASION RESISTANT



EASY SLIDE



TRANSPARENT CONSTRUCTION



WATER



“Bark Hose” BARK™ Series Standard Duty PVC Material Handling Hose

General Applications:

- Lawn and leaf collection
- Material handling – standard duty
- Mulch, bark, wood chips and other surfacing material delivery
- Soil, seed and compost delivery

Construction: PVC tube with rigid PVC helix.

Service Temperature Range:

-4°F (-20°C) to +150°F (+65°C)*

Features and Advantages:

- **Abrasion Resistant PVC Tube** – Formulated from highly durable PVC compounds for increased abrasion and tear resistance versus standard PVC hoses.
- **Convolutd Outer Cover** – Provides increased hose flexibility. Allows for easier unwinding and winding on hose reels.
- **Easy Slide Helix** – Rigid helix design protects hose tube from cover wear, and allows hose to slide easily over rough surfaces. Easy-to-handle.
- **Transparent Construction** – “See-the-flow.” Allows for visual confirmation of material flow.
- **Phthalate Free**

Nominal Specifications

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
BARK400	4	101.6	4.45	113.0	18	11	15	10	10	100	0.95
BARK500	5	127.0	5.47	138.9	17	10	14	8	11	100	1.29

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.

PHthalate FREE⁽¹⁰⁾, RoHS⁽¹¹⁾

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

