



GREASE BANDIT



GBAND™ Series

Oil Resistant Grease Trap Hose

General Applications:

- Food oil transfer
- Grease traps

Construction:

Dual profile construction with durable HDPE outer cover and proprietary oil resistant inner liner.

Service Temperature Range:

-40°F (-40°C) to +150°F (+65°C)*

Features and Advantages:

- **Grease Resistant** – Proprietary, oil resistant liner specifically designed to withstand the damaging effects of grease. Won't dry out and crack like other hoses.
- **Superior Flexibility** – Corrugated tube and ribs provides high flexibility, perfect for maneuvering in tight areas.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.



- **Crush Resistant** – Will spring back to original shape after being crushed, will not kink!
- **Easy Slide Helix** – Exposed ribs protect hose tube from cover wear, and allow hose to slide easily over rough surfaces. Easy-to-handle.

Additional Cuffs

Part Number	ID (in)	Weight (lbs)
GBCUFF150	1 1/2	0.18
GBCUFF200	2	0.20



Nominal Specifications

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Vacuum Rating Hg at 68°F (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
GBAND150	1 1/2	38.1	1.90	48.3	23	1	30/50	0.26
GBAND200	2	50.8	2.40	61	17	1.75	25/30/50	0.32

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

*Actual service temperature range is application dependent.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.