

## The World's TOUGHEST Fire Hose

### COLOR:



### General Applications:

- Active municipal departments
- Heavy industrial municipalities
- Refining, chemical and utility industries
- Coarse, abrasive landscapes
- Marine environments
- Daily use applications such as wash down and sewage treatment plants

### Construction:

Revolutionary co-extrusion technology creates a “Four Layer Hose-In-One Operation” without the use of glues or adhesives thereby forming a homogeneous hose which cannot delaminate.

### Service Temperature Range:

-4°F (-20°C) to +176°F (+80°C)

### Features and Advantages:

- Resists burn-through.
- Super resistant to abrasion.
- Underwriters Laboratories (UL) 19 and Underwriters Laboratories of Canada (ULC) – S511-14 Certified\* – 1 1/2", 1 3/4", 2", 2 1/2".
- Excellent resistance to heat, ozone, weather, most chemicals (acids, bases, salts, oils, solvents, etc.), flame, wear, tear and puncture.
- Highly flexible and smooth inner lining provides excellent dilation characteristics with low friction loss and high kinking resistance.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- ISO 9001 - JAFx4 fire hose products are manufactured in a registered facility in Barcelona, Spain.
- 10-year warranty.

### Packaging:

Available in 25', 50' and 100' lengths.



BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

### Bulk Hose Lengths

Nominal Specifications								
Part Number*	Size (in)	Color	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
56H1FX4-XX	1	Yellow	1 3/16	580	1160	1740	25/50/100	0.160
56H15FX4-XX	1 1/2	Yellow	1 3/4	300	600	900	25/50/100	0.296
56H175FX4-XX	1 3/4	Yellow	2 1/16	300	600	900	25/50/100	0.343
56H2FX4-XX	2	Yellow	2 9/32	300	600	900	25/50/100	0.390
56H25FX4-XX	2 1/2	Yellow	2 13/16	300	600	900	25/50/100	0.517
56H4FX4-XX	4	Yellow	4 9/32	250	500	750	25/50/100	0.874
56H5FX4-XX	5	Yellow	5 3/8	250	500	750	25/50/100	1.109

\*XXX = Available Lengths

### Assembled Lengths

Nominal Specifications										
Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
JX100YXXX-NH100	1	Yellow	1	NST	1 3/16	580	1160	1740	25/50/100	0.160
JX100YXXX-NP100	1	Yellow	1	NPSH	1 3/4	580	1160	1740	25/50/100	0.160
JX150YXXX-NH150	1 1/2	Yellow	1 1/2	NST	1 3/4	300	600	900	25/50/100	0.296
JX150YXXX-NP150	1 1/2	Yellow	1 1/2	NPSH	1 3/4	300	600	900	25/50/100	0.296
JX175YXXX-NH150	1 3/4	Yellow	1 1/2	NST	2 1/16	300	600	900	25/50/100	0.343
JX175YXXX-NP150	1 3/4	Yellow	1 1/2	NPSH	2 1/16	300	600	900	25/50/100	0.343
JX200YXXX-NH150	2	Yellow	1 1/2	NST	2 9/32	300	600	900	25/50/100	0.390
JX200YXXX-NP150	2	Yellow	1 1/2	NPSH	2 9/32	300	600	900	25/50/100	0.390
JX250YXXX-NH250	2 1/2	Yellow	2 1/2	NST	2 13/16	300	600	900	25/50/100	0.517
JX400YXXX-SZ400	4	Yellow	4	Storz	4 9/32	250	500	750	25/50/100	0.874
JX500YXXX-SZ500	5	Yellow	5	Storz	5 3/8	225	450	675	25/50/100	1.109

\*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.