# E6K - Alfabiotech Evolution 6000 MINETUFF

NEW

Alfabiotech Evolution 6000 MINETUFF - E6K Hydraulic Hose







### E6K - 4 or 6 wire spiral

Exceeds EN856 4SP sizes 1/4", 3/8" and 1/2"

Exceeds EN856 4SH sizes 3/4" and 1" Exceeds SAE 100R15 sizes 1" through 2"

ISO 18752/CC 1,000,000+ impulse cycles all sizes

MSHA IC-152/16 approved flame resistance



### **General Applications:**

4 ALFAGOMMA®

Developed to withstand very demanding conditions very high performance in pressure, pulsing and flexing.

#### **Construction:**

**Tube** – Oil resistant synthetic rubber and biodegradable hydraulic fluids.

Reinforcement – Four/six high tensile steel spirals.

Cover - Abrasion, ozone and hydrocarbon resistant synthetic rubber.

## **Service Temperature Range:**

-40°F (-40°C) to +250°F (+121°C)

### **Branding:**

ALFAGOMMA ALFABIOTECH EVOLUTION 6K MINETUFF ... WP 45 MPa (6550 PSI) - ISO 18752/CC- MSHA IC- 152/16 - MADE IN ITALY

#### Length:

Random up to 1" - 200 feet from 1 1/4" to 1 1/2" - 100 feet for 2"

Nominal Specifications														
Series Number	Size Code	ID		OD		Max	Min. Bend. Radius		• • • • • • • • • • • • • • • • • • •	Coupling Recommendations				
		(in)	(mm)	(in)	(mm)	Working <sup>†</sup> Pressure (psi)		(mm)	Weight (lbs/ft)	AlfaC One-I	rimp Piece	Two- Ferrule Skive		rule lock
E6K	4	1/4	6.4	0.67	17.0	6000	2.36	60.0	0.35	S		AS4		
E6K	6	3/8	9.5	0.78	19.8	6000	2.95	75.0	0.42	S		AS4		
E6K	8	1/2	12.7	0.89	22.5	6000	3.54	90.0	0.48	S		AS4		
E6K	10	5/8	15.9	1.09	27.8	6000	3.94	100.0	0.80	S			XF1	YS1
E6K	12	3/4	19.1	1.20	30.6	6000	4.72	120.0	0.93	S	F		XF2	YS2
E6K	16	1	25.4	1.50	38.2	6000	5.91	150.0	1.30	S	F		XF2	YS2
E6K	20	1 1/4	31.8	1.87	47.6	6000	8.86	225.0	2.01	S	F		XF1	YS1
E6K	24	1 1/2	38.1	2.14	54.4	6000	12.01	305.0	2.80	S			XF1	YS1
E6K	32	2	50.8	2.70	68.7	6000	14.96	380.0	4.09				Z	F1

<sup>†</sup> Minimum burst pressure 4-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.