



VRP-A Series (Aluminum Part C w/Probe)

Female Coupler X Hose Shank

VRP-P Series (Aluminum Part C w/Poppet)

Female Coupler X Hose Shank

DAP Series (Aluminum Part C w/Probe)

Female Coupler X Male Coupler

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/VAPOR

GENERAL APPLICATIONS

Kuriyama Camlock Couplings are intended for use in many industrial applications. To learn more, please refer to pages 296-297 in this catalog.

FEATURES AND ADVANTAGES

- High quality design made for use in petroleum markets with bottom loading applications.
- Each coupling comes with a probe for connecting with male vapor coupling.
- Aluminum alloy specially designed for high tensile strength and impact resistance.
- Supplied with forged brass handles, which results in less wear on connecting parts.

MATERIAL SPECIFICATIONS

- ASTM aluminum alloy.
- Zinc-plated carbon steel handle pins, pull rings and safety clips.
- Supplied with brass probe.
- Buna-N gasket included.

Part Number	Coupler Size (in)	Shank Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
VRP-A4030	4	3	150	B26 Grade 713	3.04	4
VRP-A4040	4	4	150	B26 Grade 713	3.15	4

Part Number	Coupler Size (in)	Shank Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
VRP-P4030	4	3	150	B26 Grade 713	4.01	5

Part Number	Female Coupler Size (in)	Male Coupler Size (in)	PSI Rating at 70°F	ASTM Specification	Weight Each (lbs)	Standard Carton
DAP-4030	4	3	150	B26 Grade 713	3.54	4

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.